


DS-2CD2T22-15



HIKVISION



The Hikvision DS-2CD2T22-15 is a 2 megapixel (1920 x 1080) IR bullet camera with a 4mm lens. The camera has built in IR with a range of up to 50m and is housed in an IP66 rated enclosure. It uses a high performance LED benefiting from an advanced, highly efficient light source that provides up to 30% more illumination efficiency compared to other LEDs, and a revolutionary rectangular lens for uniform scene illumination and seamless HD formatting. Hikvision's EXIR cameras deliver the most advanced levels of night time surveillance available on the market today. The camera can be powered over ethernet (PoE) for quick and easy installation when used with the plug and play features of our Hikvision NVRs.

FEATURES:

- **2 megapixel high resolution**
- **Full HD 1080p real-time video**
- **4mm fixed lens**
- **EXIR illuminator (up to 50m)**
- **DWDR, 3D DNR & BLC**
- **IP66**
- **PoE**

Example of brackets available

DS-1260ZJ
Power intake box
Ø88.5mm

DS-1280ZJ-S
Junction box
137 x 51.5mm

DS-1276ZJ
Corner mount
158 x 173mm

DS-1275ZJ
Vertical pole mount
117 x 143 x 194mm

Dimensions Unit: mm (inch)

DS-2CD2T22-15	
CAMERA	
Image Sensor	1/3" Progressive Scan CMOS
Min. Illumination	0.01 lux @(F1.2,AGC ON), 0 lux with IR 0.014 lux @(F1.4,AGC ON), 0 lux with IR
Shutter Time	1/3 s to 1/100,000 s
Slow Shutter	Support
Lens	4mm @ F2.0
Lens Mount	M12
Day & Night	ICR
Wide Dynamic Range	Digital WDR
COMPRESSION STANDARD	
Video Compression	H.264/MJPEG
H.264 Codec Profile	Main Profile
Bit Rate	32 Kbps ~ 12 Mbps
IMAGE	
Max. Image Resolution	1920 x 1080
Frame Rate	50Hz: 25fps(1920 x 1080) 25fps(1280 x 960) 25fps(1280 x 720) 60Hz: 30fps(1920 x 1080), 30fps(1280 x 960) 30fps(1280 x 720)
Image Enhancement	BLC/3D DNR/ROI
Image Settings	Rotate mode, Saturation, Brightness, Contrast adjustable by client software or web browser
Day/Night Switch	Auto/Schedule/Triggered by alarm in
NETWORK	
Network Storage	NAS (Support NFS, SMB/CIFS)
Alarm Trigger	Intrusion detection, Line crossing detection, Motion detection Dynamic Analysis, Tampering alarm, Network disconnect, IP address conflict, Storage exception
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, Ipv6, Bonjour
Security	Flash-prevention, dual stream, heartbeat, mirror, password protection, privacy mask, watermark, IP address filtering, Anonymous access
General	ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI
INTERFACE	
Communication Interface	1 RJ45 10M / 100M Ethernet interface
GENERAL	
Operating Conditions	-30 °C ~ 60 °C (-22°F ~ 140 °F) humidity 95% or less (non-condensing)
Power Supply	12 VDC ± 10% , PoE (802.3af)
Power Consumption	Max. 7.5W
Ingress Protection Level	Ip66
IR Range	2pcs EXIR LEDs, up to 50m
Dimensions	299.71 x 86.48 x 85.11mm (11.8" x 3.4" x 3.35")
Weight	1200g (2.65 lbs)